

Warranty Registration & Start-Up Report

Please Circle o	or Highlight									
Model:	MicroFAST _®	HighStrengthFAST _®		RetroFAST®		NitriFAST _®		LagoonFAST _®		
Model Size	e: 0.25	0.375	0.5	0.75	0.9	1.0	1.5	3.0	4.5	9.0
Serial Num	Serial Number:				Da	ite of Ins	stallatio	n:		
			IN	NSTALI	LATIO	N SITE				
NAME	NAME		Company:							
ADDRESS	ADDRESS									
CITY/STAT	TE/ZIP									
PHONE/F	ΑX									
	(OWNER	(if dif	ferent th	ıan INS	TALLA	ATION	SITE)		
NAME		Company:								
ADDRESS										
CITY/STAT	CITY/STATE/ZIP									
PHONE/F	AX									
		В	IO-MI	CROBI	CS' DI	STRIBU	U TOR			
NAME		F	Peterser	n Supply						
ADDRESS		PO Box 340, 421 Wheeler Avenue								
CITY/STATE/ZIP		Fredonia, WI 53021-0340								
PHONE/FAX		262-692-2416 262-692-2418								
			INS	TALLE	ER			SER	VICE F	PROVIDER
NAME										
ADDRESS	3									
CITY/STAT	CITY/STATE/ZIP									
PHONE/FA	AX									
		CON	<u>SU</u> LT	ING EN	<u>IGI</u> NEI	ER (if a _l	oplicab	le)_		
NAME										
ADDRESS	i									
CITY/STAT	TE/ZIP									
PHONE/FAX										

Please mail or fax completed form to Petersen Supply, PO Box 340, OVEr→ Fredonia, WI 53021 Tel: 888-455-6864 Fax: 800-669-1232. Thank you.

A	Complete this section ONLY if the FAST® was installed in tank at the jobsite.										
	Tank Manufacturer:	Т	Tank Model No								
	Working Liquid Volume in Trash Collector Char										
	Working Liquid Volume in FAST Treatment Cha	amber:									
	FAST system installed using which method:			Lid Suspension							
	(Check one - FAST system installed into tank by wh	Leg Support									
В	Tankage	Yes	No	Service & Access Ports	Yes	No					
Concrete Tank Fiberglass Tank Anti-Flotation Installed H ₂ O Loading Capabilities Fill Over FAST Lid Tank Level Watertight Joints & Piping				Trash Tank Clean Out Present FAST Chamber Clean Out Preser Trash Tank Vent Inspection Port Access to Grade							
С	Alarm Panel/Piping	Yes	No								
Visual Element Operating Audio Alarm Operating Sensor Switch Installed				Length of Air Supply Line: Diameter of Air Supply Line:							
D	Air Blower	Yes	No		Yes	No					
	Filter Element Inside Blower Hood Installed Blower Hood Secure Blower Area Ventilated Wired for High of Low Voltage (Circle Voltage: Brand:		Blower Operates Correctly								
E	Treatment Unit	Yes	No		Yes	No					
Air Lift Operates Correctly Module Insert Stable 4" Outlet Pipe Placed Length of Vent Line:				Remote or Inspection Port Vent Module Sealed & Bolted to Tank Air Line Connection Glued to Airlift Size of Vent Line Pipe:							
F	Treatment Unit	Yes	No		Yes	No					
	Manuals Onsite for Owner Warranty to Owner			NSF Inspection Service Given to Owner After NSF Service Contract to Owner							
G				System Components and Configurati Sheets if Necessary)	ons						
	* Product Registration Report must be										